

**POLYAMIDE PA6.6 CABLE TIES  
G SERIES****Polyamide PA6.6 cable ties main features:**

Material: POLIAMYDE PA6.6

- Self extinguishing cl.V2 (UL 94)
- Humidity absorption: 2,5% (at 50% of relative humidity )
- Working temperature: -40°C to +85°C (continuous)  
-40°C to +120°C (short periods)
- Resistance to external agents: oils, bases, greases, oil products, chlorinated solvents
- Colour: Natural and Black (Ral 9005)

**Cembre SpA**


Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: [www.cembre.com](http://www.cembre.com) - Email: [info@cembre.com](mailto:info@cembre.com)

**CABLE TIES G SERIES  
Polyamide PA6.6**
**Cable Ties in PA6.6**

Type	L (mm)	A (mm)	Max. Bundle Ø (mm)	Min. Loop Tensile Strength (kg)	Quantity	
G80X2.4	80	2,4	15	8	100	
G80X2.4N					16	1000
G80X2.4/M			22			100
G80X2.4N/M					30	1000
G90X2.4	140	33	100			
G90X2.4N			40			1000
G100X2.5		53				1000
G100X2.5N			2,5		100	
G100X2.5/M	65	1000				
G100X2.5N/M		76			1000	
G120X2.5	120				30	100
G120X2.5N		33	1000			
G140X2.5			35	1000		
G140X2.5N		44		1000		
G140X2.5/M	160		53	100		
G140X2.5N/M		65		1000		
G160X2.5			76	1000		
G160X2.5N		200		102	100	
G160X2.5/M	124		1000			
G160X2.5N/M			2,8	30	1000	
G200X2.5	33				14	100
G200X2.5N		35		18		1000
G200X2.5/M	44					30
G200X2.5N/M		53	33			
G250X2.8	250				65	
G250X2.8N		76		18		
G300X2.8					102	22
G300X2.8N		124	24			
G300X2.8N/M	120				24	
G120X3.6		38		22		
G120X3.6N					46	22
G140X3.6		50	22			
G140X3.6N	60				22	
G140X3.6/M		76		22		
G140X3.6N/M	102					22
G150X3.6		124	22			
G150X3.6N	150				22	
G180X3.6		190		22		
G180X3.6N	200					22
G200X3.6		250	22			
G200X3.6N	370				22	
G200X3.6/M		120		22		
G200X3.6N/M	160					22
G250X3.6		190	22			
G250X3.6N	200				22	
G300X3.6		250		22		
G300X3.6N	250					22
G300X3.6/M		250	22			
G300X3.6N/M	250				22	
G370X3.6		250		22		
G370X3.6N	250					22
G120X4.8		250	22			
G120X4.8N	250				22	
G160X4.8		250		22		
G160X4.8N	250					22
G190X4.8		250	22			
G190X4.8N	250				22	
G190X4.8/M		250		22		
G190X4.8N/M	250					22
G200X4.8		250	22			
G200X4.8N	250				22	
G200X4.8/M		250		22		
G200X4.8N/M	250					22
G250X4.8/M		250	22			
G250X4.8N/M	250				22	



Minimum order: 1000 pcs

Note: In Type, N = Black

**Cembre SpA**


Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: info@cembre.com

**CABLE TIES G SERIES  
Polyamide PA6.6**
**Cable Ties in PA6.6**

Type	L (mm)	A (mm)	Max. Bundle Ø (mm)	Min. Loop Tensile Strength (kg)	Quantity
G250X4.8	250	4,8	60	22	100
G250X4.8N					
G280X4.8	70				
G280X4.8N					
G300X4.8	76				
G300X4.8N					
G370X4.8	102				
G370X4.8N					
G390X4.8	105				
G390X4.8N					
G430X4.8	110				
G430X4.8N					
G450X4.8	116				
G450X4.8N					
G530X4.8	140				
G530X4.8N					
G150X7.6	150	7,6	33	55	
G150X7.6N					
G200X7.6	50				
G200X7.6N					
G250X7.6	65				
G250X7.6N					
G300X7.6	76				
G300X7.6N					
G370X7.6	102				
G370X7.6N					
G430X7.6	125				
G430X7.6N					
G530X7.6	140				
G530X7.6N					
G430X9.0	430	9,0	110	80	
G430X9.0N					
G530X9.0	140				
G530X9.0N					
G710X9.0	190				
G710X9.0N					
G780X9.0	228				
G780X9.0N					
G830X9.0	239				
G830X9.0N					
G920X9.0	263				
G920X9.0N					
G1020X9.0	295				
G1020X9.0N					
G1220X9.0	365				
G1220X9.0N					
G230X12.6	230	12,6	50	115	
G230X12.6N					
G380X12.6	106				
G380X12.6N					
G480X12.6	120				
G480X12.6N					
G580X12.6	152				
G580X12.6N					
G730X12.6	204				
G730X12.6N					
G880X12.6	248				
G880X12.6N					
G1030X12.6	295				
G1030X12.6N					



Minimum order: 100 pcs

Note: In Type, N = Black

**Cembre SpA**

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

Web: www.cembre.com - Email: info@cembre.com