

CABLE TIES GX

in Stainless Steel AISI 304

Unique ball locking mechanism that allows simple and rapid installation and secure locking. High tensile strength. Non-flammability. High resistance to acetic acid, alkalies, sulphuric acid, corrosion, etc. In general very resistant to most hostile environments.



CERTIFICATES 



2011/65/EU

CABLE TIES GX

Technical characteristics

Min operating temperature range	-112 °F
Max operating temperature range	932 °F
Material	Stainless steel AISI 304



CABLE TIES GX

List of products

GX



Type	A	L	Maximum outside diameter	Pack qty	Minimum loop tensile strenght
GX200X4.5	0.18 in.	7.87 in.	1.97 in.	100	101.2 lbs.
GX300X4.5	0.18 in.	11.81 in.	2.99 in.	100	101.2 lbs.
GX370X4.5	0.18 in.	14.57 in.	4.02 in.	100	101.2 lbs.
GX520X4.5	0.18 in.	20.47 in.	6.14 in.	100	101.2 lbs.
GX370X7.9	0.31 in.	14.57 in.	4.02 in.	100	250.8 lbs.
GX680X7.9	0.31 in.	26.77 in.	8.15 in.	100	250.8 lbs.
GX1020X7.9	0.31 in.	40.16 in.	12.28 in.	100	250.8 lbs.

Products used together

Tools

CABLE TIE TOOL 55270 - 5527030079