

LOCKNUTS WITHOUT COLLAR 1710

Polyamide PA6.6


Pg thread DIN 40 430 - Dimensions DIN 46 320



LOCKNUTS WITHOUT COLLAR 1710

Technical characteristics

Material (Body)	Polyamide PA6.6
UL94 class	V2
Min operating temperature range	-4 °F
Max operating temperature range	194 °F



LOCKNUTS WITHOUT COLLAR 1710

List of products

1710



Type	Thread	Opening key (for the head)	Height	Pack qty	Min. pack qty	Color
1719E17	Pg7	0.67 in.	0.2 in.	1,000	100	Grey RAL 7035
1719	Pg7	0.75 in.	0.2 in.	100	100	Grey RAL 7035
1710	Pg9	0.87 in.	0.2 in.	700	100	Grey RAL 7035
1711	Pg11	0.94 in.	0.2 in.	500	100	Grey RAL 7035
1712	Pg13,5	1.06 in.	0.24 in.	400	100	Grey RAL 7035
1713	Pg16	1.18 in.	0.24 in.	300	100	Grey RAL 7035
1714E34	Pg21	1.34 in.	0.28 in.	200	100	Dark Grey RAL 7001
1714	Pg21	1.42 in.	0.28 in.	200	100	Grey RAL 7035
1715	Pg29	1.81 in.	0.3 in.	100	25	Grey RAL 7035
1719E17N	Pg7	0.67 in.	0.2 in.	1,000	100	Black RAL 9005
1719N	Pg7	0.75 in.	0.2 in.	100	100	Black RAL 9005
1710N	Pg9	0.87 in.	0.2 in.	700	100	Black RAL 9005
1711N	Pg11	0.94 in.	0.2 in.	500	100	Black RAL 9005
1712N	Pg13,5	1.06 in.	0.24 in.	400	100	Black RAL 9005
1713N	Pg16	1.18 in.	0.24 in.	300	100	Black RAL 9005
1714N	Pg21	1.42 in.	0.28 in.	200	100	Black RAL 9005
1715N	Pg29	1.81 in.	0.3 in.	100	50	Black RAL 9005