

## SINGLE POLE TERMINAL BLOCKS Z6-3

*indirect clamping  
nominal section 10 AWG*

3, 5, 6 and 10 way, single pole terminal blocks for conductor section 17 to 10 AWG. Self contained and robust, they are quick and easy to install for both industrial and domestic use. The indirect clamping of the "ZETApiù" terminal blocks guarantees a low and stable contact resistance. Indirect clamping eliminates damage to the conductor strands. The easy-entry receptacles also grant a fast and reliable insertion of the cable.



CERTIFICATES 



CEI EN 60998-1



EN 60998-1



EN 60998-2-1

1:1993



EN 60998-1:2004



EN 60998-1:2004



EN 60998-2-



EN 60998-2-1: 2004

# SINGLE POLE TERMINAL BLOCKS Z6-3

## *Technical characteristics*

### PROPERTIES

Height	1.08 in.
Width	0.91 in.
Length	0.91 in.
Number the hole	3
Pack qty	30
Weight	0.03 lbs.
Easy entry	yes
UL94 class	V0
Halogen Free	yes
Max application temperature	185 °F
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned
IP protection	20

